

# MPPT RS SMARTSOLAR

MPPT RS SmartSolar is a Photovoltaic Solar charge controller with a PV input up to 450VDC and an output at 48 VDC and a charging capacity up to 100 or 200 A output, depending of the model.



Victron MPPT RS



Victron MPPT RS



Victron MPPT RS



Victron MPPT RS



Victron MPPT RS

### Ultra-fast Maximum Power Point Tracking (MPPT) Solar Charge Controller

The MPPT RS SmartSolar is a 48V Solar charge controller with up to 450VDC PV input and 100 or 200 A output. It is used in on-grid and off-grid solar applications where maximum battery charging power is required.

### Multiple independent MPPT tracking inputs

With multiple MPPT trackers, you can optimize your solar panel design for maximum performance for your specific location.

### Isolated PV connections for additional safety

Full galvanic isolation between PV and battery connections provide additional overall system safety.

### Wide MPPT voltage range

80 – 450 VDC PV operating range, with a 120VDC PV startup voltage.

### Light weight, efficient and quiet

Thanks to high frequency technology and a new design this powerful charger weighs only 7.9 kg. In addition to this it has an excellent efficiency, low standby power, and a very quiet operation.

### Display and Bluetooth

The display reads battery, and solar charge controller parameters.

The parameters can be accessed with a smartphone or other Bluetooth enabled device. In addition, Bluetooth can be used to set up the system and to change settings with VictronConnect.

### PV Isolation resistance monitoring for peace of mind at higher voltages

The MPPT RS continuously monitors the PV array and can detect if there are faults that reduce the isolation of the panels to unsafe levels.

### VE.Can and VE.Direct port

For connection to a GX device for system monitoring, data logging, and remote firmware updates. VE.Can allows for up to 25 units to be connected together in parallel and synchronize their charging.

### I/O Connections

Programmable Relay, temperature sensor, auxiliary, digital input and voltage sensor connections. The remote input can accept the Victron smallBMS, and other BMS with allow-to-charge signal.

Configure and monitor with VictronConnect

A built-in Smart Bluetooth connection allows for quick monitoring or settings adjustment of the MPPT RS.

The built in 30 day history shows individual performance of the separate MPPT trackers.

Try the VictronConnect demo to see the full range of configuration and display options with sample data.

### VRM Portal

When the MPPT RS is connected to a GX device with internet connection, or the GlobalLink 520 with built in 4G connectivity, you can access our free remote monitoring website (VRM).

This will display all your system data in a comprehensive graphical format.

Alarms can be received by e-mail.

# SPECIFICATIONS

SmartSolar MPPT RS	450/100	450/200
<b>Charger</b>		
Programmable charger voltage range		Minimum: 36 V Maximum: 62 V
Charge voltage 'absorption'		default: 57,6 V
Charge voltage 'float'		default: 55,2 V
Maximum charge current	100 A	200 A
Battery temperature sensor		Included
<b>Solar</b>		
Maximum DC PV voltage		450 V
Start-up voltage		120 V
MPPT operating voltage range		80 - 450 V (1)
Number of MPPT trackers	2	4
Maximum operational PV input current		18 A per MPPT tracker
Max. PV short circuit current reverse polarity protection (2)		20 A per MPPT tracker
Maximum DC output charging power	4000 W per MPPT tracker 11520 W total 100 A at 57,6 V	4000 W per MPPT tracker 11520 W total 200 A at 57,6 V
Maximum PV array size per tracker (3)		7200 Wp (450V x 20 A) (3)
PV Isolation fail level (4)		100 kΩ
<b>General</b>		
Synchronised Parallel Operation		Yes, up to 25 units with VE.Can
Programmable relay	General alarm, DC under voltage or genset start/stop function. DC rating: 4A up to 35VDC and 1A up to 70VDC	
Protection	Battery voltage too high Battery voltage too low Temperature too high	
Data communications	VE.Direct port, VE.Can port & Bluetooth (5)	
General purpose analogue / digital in port	Yes, 2x	
Remote on-off	Yes	
Operating temperature range	-40 to 65 °C (fan assisted cooling)	
Humidity (non-condensing)	max. 95 %	
<b>Enclosure</b>		
Material & Colour	Steel, blue RAL 5012	
Protection category	IP22	
Battery-connection	M8 bolts	
Weight	7,9 Kg	13,7 Kg
Dimensions (h x w x d)	440 x 313 x 126 mm	487 x 434 x 146 mm
<b>Standards</b>		
Safety	EN-IEC-62109-1, EN-IEC-62109-2	

1) MPPT operating range is also constrained by battery voltage - PV VOC should not exceed 8x battery float voltage. For example, a 52,8V float voltage results in a maximum PV VOC of 422,4V. See product manual for further information.

2) A higher short circuit current may damage the controller if PV array is connected in reverse polarity.

3) Max. 450 Voc result in appr. 360 Vmpp, therefor the maximum PV array is appr. 360V x 20A = 7200Wp

4) The MPPT RS will test for sufficient resistive isolation between PV+ and GND, and PV- and GND. In the event of a resistance below the threshold, the unit will stop charging, display the error, and send the error signal to the GX device (if connected) for audible and email notification.

5) The MPPT RS is not currently compatible with VE.Smart Networks