

COPACT SINGLE PHASE

SolarEdge develop the single phase inverter with compact technology is a cost-effective DC-optimized inverter solution for small rooftop systems of 4-8 modules. It is ideally suited for homes with limited roof space, social housing projects, or for meeting minimum sustainability requirements.



SolarEdge Compact

The **single phase inverter** with compact technology is a cost-effective DC-optimized inverter solution for small rooftop systems of 4-8 modules. It is ideally suited for homes with limited roof space, social housing projects, or for meeting minimum sustainability requirements.

Featuring many **SolarEdge** benefits such as greater energy harvest from each module, long-term product warranties, advanced safety features, and free module-level monitoring¹, the single phase inverter with compact technology is easily installed on either existing rooftops or new buildings, and delivers clean energy which is affordable, efficient, and safe.

Cost-effective solution for residential systems of 4-8 modules

- Each of the four power optimizer inputs supports one or two 60-cell modules, or one 72/96-cell modules
- Suitable for homes with limited roof space, social housing projects, or for meeting minimum sustainability requirements
- Extremely compact, lightweight, and easy to install
- IP65 rated inverter — suitable for indoor or outdoor installation
- Power optimizer and inverter designed to work exclusively with each other and are ordered with a single part number and supplied in a single box
- Optional communication option for maximum cost effectiveness

INVERTERS

		SE1000M	SE1500M	SE2000M
Output				
Maximum AC Power output	VA	1000	1500	2000
AC Output voltage (nominal)	Vac		220 / 230	
AC Output voltage range	Vac		184 - 264,5	
Maximum continuous output current	A	5	7	9,5
Input				
Maximum DC power	W	1350	2025	2640
Transformer-less, ungrounded			Yes	
Maximum input voltage	Vdc		500	
Operating voltage	Vdc		75 - 480	
Maximum input current	Adc		11	
Maximum inverter efficiency			97 %	
European Weighted efficiency		95,7 %	96,5 %	97 %
Additional Features				
Supported Communication interfaces		Basic: No Communication Interfaces Extended: RS485 Interface, communication to SolarEdge monitoring platform via built-in Ethernet or Wi-Fi(1) connectivity, or additional options purchased separately such as ZigBee or GSM plug-ins		
Smart Energy Management		Basic: No Smart Energy Management Extended: Export Limitation, Home Energy Management		
Standard				
Safety		IEC-62103 (EN50178), IEC-62109		
Grid Connection		VDE-AR-N-4105, VDE 0126-1-1, AS-4777, RD-1663, DK5940		
Emissions		IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part 15 class B		
RoHS		Yes		
Installation specifications				
Dimensions	mm	340 x 239 x 127		
Noise	dBA	< 25		
Weight	Kg	6		
Cooling		Natural Convection		
Operating Temperature Range		-40 to 60 °C		
Protection Rating		IP65		

(1) Wi-Fi connectivity requires an external antenna.

OPTIMIZER

M2640		
(For 4-8 60-cell modules or 4 72-cell / 96-cell modules)		
Input		
Number of inputs		4
Number of MPP Trackers		4 (one per input)
Rated DC power per unit	W	660
Absolute max Input voltage (Voc at lowest temp)	Vdc	96
MPPT per input operating range	Vdc	12,5 - 80
Maximum Short Circuit Current per input (Isc)	Adc	10,5
Maximum Efficiency		99,5 %
Weighted Efficiency		98,8 %
Output during operation		
Maximum output current	Adc	10,5
Maximum output voltage	Vdc	340
Output during Standby		
Safety output voltage per power optimizer	Vdc	10 ± 1
Installation specifications		
Maximum allowed system voltage	Vdc	600
Dimensions	mm	152 x 211 x 60
Weight (including cables)	Kg	1,5
Input connector		4 x MC4 Pairs
Output connector		1 x MC4 Pair
Operating temperature range		-40 to 85 °C
Protection Rating		IP68

		SE1000M	SE1500M	SE2000M
PV System Design				
Number of M2640 per inverter			1	
Maximum DC System power	Wdc	1350	2025	2640

DOWNLOADS

CATÁLOGO GENERAL 2020

 [Catalogo-Bornay-0520.pdf](#)

Size: 21.51 MiB