

# SMA HOME STORAGE

The SMA Home Storage Solution allows homeowners to unlock the full potential of sustainable energy. Integrating the SMA Home Storage battery makes the modular solution complete: everything from a single source. It perfectly complements SMA's hybrid inverters enabling energy solutions of today and tomorrow.



SMA Home Storage



SMA Home Storage



SMA Home Storage



SMA Home Storage



SMA Home Storage

Whether during times of low solar irradiation or the highs of midday - the SMA Home Storage can store solar power and make it available as needed.

It offers flexible scalability to be adapted to individual needs and has an especially long lifetime of around 8000 charging cycles.

With the SMA Home Storage, homeowners are making a conscious choice for quality and additional security with the 10-year warranty<sup>1)</sup>.

### Future-proof electricity storage system

- Developed for intensive use
- Ready for future, like dynamic tariffs and virtual power plants (VPP)
- Integrated black start function for back-up supply (when combined with the SMA hybrid inverter)
- 8000 life cycles and 10 years of warranty<sup>1)</sup>

### Easy installation, fast commissioning

- Plug and play solution, including automatic commissioning
- Preassembled cables for an easy installation
- Expandable capacity possible within 2 years

### Unmatched flexibility

- Compatible with SMA's hybrid inverters
- Slim, stackable design that can be scaled from 3.2 kWh to 16.4 kWh
- Floor, wall or back-to-back mounting
- Outdoor installation possible (Protection class IP65)

<sup>1)</sup> Device registration via the SMA product registration at [my.sma-service.com](http://my.sma-service.com) required within 30 days. The conditions of the SMA limited factory warranty apply.

## SPECIFICATIONS

	SMA Home Storage 3.2	SMA Home Storage 6.4	SMA Home Storage 9.6	SMA Home Storage 12.8	SMA Home Storage 16.0
<b>Electrical Data</b>					
Usable energy capacity <sup>1)</sup> (kWh)	3,28 kWh	6,56 kWh	9,84 kWh	13,12 kWh	16,4 kWh
Nominal voltage <sup>2)</sup> (V)	96 V	192 V	288 V	384 V	480 V
Operating voltage range (V)	90 - 108 V	180 - 216 V	270 - 324 V	360 - 432 V	450 - 540 V
Max. charging / discharging current (A)	36 / 36 A	36 / 36 A	36 / 36 A	36 / 36 A	36 / 36 A
<b>General data</b>					
Dimensions ( W / H / D ) mm	610 x 483 x 214,6	610 x 969 x 214,6	610 x 1455 x 214,6	2 x (610 x 969 x 214,6)	610 x 1455 x 214,6 y 610 x 969 x 214,6
Weight	38	76	114	152	190
Operating temperature range	-10 to +50 °C				
Self-consumption(at night) per module	2 W				
Protection degree	IP65				
Max. permissible relative humidity	5 to 95 % (non condensing)				
Cell Technology	LiFePO4				
<b>Protective Devices</b>					
Input-side disconnection point	Yes				
DC Reverse polarity protection	Yes				
Protection degree	I				
Overvoltage category battery	II / II				
<b>Equipment</b>					
DC connection	MC4				
Interface / communication	RJ45				
Communication protocols	SMA Battery interface				
Warranty 2 / 10 years	Yes / Yes <sup>3)</sup>				
Certificates and permits (more available upon request)	CE, UN 38.3, IEC 62619, IEC 62477, VDE 2510-50				
Compatible SMA Products	STE-SE, SB-SE				
<b>Accessories</b>					
	Base unit for floor mounting (HS-BU-10), communication cable to STP-SE				
Type designation	HS-BM-3.28-10	2 x HS-BM-3.28-10	3 x HS-BM-3.28-10	4 x HS-BM-3.28-10	5 x HS-BM-3.28-10

<sup>1)</sup> Under specific test conditions (100% DOD, 0.2 C charge and discharge at +25 °C).

<sup>2)</sup> Dimensions for wall mounting. Dimensions with optional base unit can be found in the product manual.

<sup>3)</sup> Device registration via the SMA product registration at my.sma-service.com required within 30 days. The conditions of the SMA limited factory warranty apply.

## DOWNLOADS

### SMA HOME STORAGE ESP

 [HS-BM-10-DS-es-10.pdf](#)

Size: 665.68 KiB

### SMA HOME STORAGE ENG

 [HS-BM-10-DS-en-11.pdf](#)

Size: 573.16 KiB