

BLUESOLAR DUO

20A at 12V or 24V *



Regulador Solar Victron Energy BlueSolar DUO



Display Regulador Solar Victron Energy BlueSolar DUO

PWM controller

- Charges two separate batteries. E.g. the starter battery and the service battery of a boat or mobile home
- Programmable charge current ratio (standard setting: equal current to both batteries)
- Charge voltage settings for three battery types (Gel, AGM and Flooded)
- Internal temperature sensor and optional remote temperature sensor
- Protected against over current
- Protected against short circuit
- Protected against reverse polarity connection of the solar panels and/or battery.

SPECIFICATIONS

BlueSolar DUO 12/24-20

Performance

Battery voltage 12 / 24 Vcc

Self-consumption 4 mA


DC input

Rated charge current 20 Amp

Maximum solar voltage	28 / 55 Vcc
MPPT tracker	No
DC Output	
Maximum load	No
Absorption voltage	14,4 / 28,8 Vcc
Float voltage	13,7 / 27,4 Vcc
Second battery output	Si
Temperature specifications	
Operating temperature	-35° C to +55 °C
Enclosure and Environmental	
Terminal size	6 mm ²
Protection class	IP20
Dimensions	70 x 153 x 37 mm
Weight	180 gr
Mounting	Vertical wall mount. Indoor only
Standards	
Safety	EN60335-1
EMC	EN61000-6-1, EN61000-6-3, ISO 7637-2

DOWNLOADS

CATÁLOGO GENERAL 2020

 [Catalogo-Bornay-0520.pdf](#) (27.76 MiB)
Size: 27.76 MiB