

VENUS GX

The Venus GX provides intuitive control and monitoring for all Victron power systems.



Venus GX



Venus GX



Venus GX



Venus GX

Venus GX

The Venus GX provides intuitive control and monitoring for all Victron power systems. The list of Victron products that can be connected is endless: Inverters, Multis, Quattros, MPPT solar

chargers, inverters, multis, quattros, multi solar chargers, BMV battery monitors, Lynx Ion + Shunt and more.

VRM Online Portal

All readings are forwarded to our free remote monitoring website: the VRM Online Portal.

Remote Console on VRM

The way to access the device for setting up, as well as monitoring, is via Remote Console. Either via VRM, via the built-in WiFi Access Point, or on the local LAN/WiFi network.

Automatic genset start/stop

A highly customizable start/stop system. Use state of charge, voltage, load and other parameters. Define a special set of rules for quiet times, and optionally a monthly test run.

The heart of ESS – Energy Storage System

The Venus GX is the Energy Manager in an ESS system.

Data logging

When connected to the internet, all data is sent to the VRM Portal. When there is no internet connection available, the Venus GX will store the data internally, up to 48 hours. By inserting a micro SD-card or USB stick, more data can be stored. These files can then be uploaded to the VRM Portal, or offline converted with the VictronConnect app, for analysis.

Supported products

- Multis and Quattros, including split-phase and three-phase systems. Monitoring and control (on/off and current limiter). Changing configuration is possible (only remotely via the internet, not without an internet connection).
- EasySolar 1600VA
- BlueSolar MPPT Solar Chargers with a VEDirect port.
- BlueSolar MPPT 150/70 and the MPPT 150/85 with VECan port.
- SmartSolar MPPT 150/70 and the MPPT 150/100 with VECan port. When multiple BlueSolar MPPTs or SmartSolar MPPTs with VECan are used in parallel, all the information is combined as one.
- BMV-700 family can be connected directly to the VEDirect ports on the Venus GX. Use the VEDirect Cable for this.
- BMV-600 family can be connected to the VEDirect ports on the Venus GX. Requires an accessory cable.
- Lynx Ion + Shunt
- Lynx Ion BMS
- Lynx Shunt VECan
- Skylla-i battery chargers
- NMEA2000 tank sensors
- A USB GPS can be connected to the USB port. The data is sent to the VRM Portal for tracking purposes. The map on VRM will show the latest position.
- Fronius PV Inverters

When more than two VEDirect products must

When more than the Victron products must be connected, USB can be used.

Internet connection

The Venus GX can be connected to internet with an Ethernet cable and via Wi-Fi. The Venus GX has no internal cellular modem: there is no slot for a sim-card. Use an off-the-shelf GPRS or 3G router instead. See the blog post about 3G routers.

Tank level inputs

The tank level inputs are resistive: connect them to a resistive tank sender. Such tank senders are not supplied by Victron. The tank level ports can each be configured to work with either European tank senders (0 - 180 Ohm), or US (240 - 30 Ohm).

Other highlights

- The Venus GX can automatically update itself from the internet, when there is a new software version available.
- Multiple languages: English, Czech, German, Spanish, French, Italian, Dutch, Russian, Swedish, Turkish, Chinese, Arabic.
- Use the Venus GX as a Modbus-TCP gateway to all connected Victron products

SPECIFICATIONS

Venus GX

Power supply voltage range	8 - 70 Vdc
Current Draw	210 mA @12V, 110 mA @24V, 60 mA @48V

Communication ports

VE.Direct	2 separate ports - isolated
VE.Can	2 paralleled RJ45 Sockets - isolated
CAN	2nd CAN interface - non isolated
VE.Bus	2 paralleled RJ45 sockets - isolated
USB	2 USB Host ports - not isolated
Ethernet	10/100/1000 RJ45 socket - isolated except shield
WiFi Access Point	Use to connect to Remote Console
Wifi Client	Connect the Venus GX to an existing WiFi network

IO

Potential free contact	NO/COM/NC - 6 A 250 Vac / 30 Vdc
Tank level inputs	3 x configurable EU (0-180 Ohm) or US (240-30 Ohm)
Temperature level inputs	2 (requires optional ASS000010000)

3rd party

3rd party interfacing

Modbus-TCP	Use ModBus TCP to monitor and controll all products connected
------------	---

JSON	Use the VRM JSON API to retrieve data from the VRM Portal
------	---

Other

Dimensions (h x w x d)	45 x 143 x 96 mm
------------------------	------------------

Operating temperature range	-20 to 50 °C
-----------------------------	--------------


Standards

Safety	EN 60950-1:2005 + A1:2009 + A2:2013
--------	-------------------------------------

EMC	EN 61000-6-3, EN 55014-1, EN 61000-6-2-, EN 55014-2
-----	---

DOWNLOADS

CATÁLOGO GENERAL BORNAY 14-15

 [Catalogo-Bornay-1415.pdf](#) (10.41 MiB)
Size: 10.41 MiB
