

Skype



ME SOLAR MODULES

Me Solar solar modules are a high efficiency monocrystalline solar panels that provides free energy for battery charge at 12 or 24 volts, in multiple applications such as in a camper van, boat, house or garden, as well as off-grid applications.



Panel Me Solar 20 W



Panel Me Solar 30 W



Panel Me Solar 50 W



Panel Me Solar 80 W



Panel Me Solar

Me Solar solar modules are a high efficiency **monocrystalline solar panels** to provide free energy for charging a 12V or 24V battery in many applications such as in a camper van, boat, house or garden, as well as off-grid for farming, lighting, telecommunications or monitoring equipment.

Me Solar modules are made using Germany SolarWorld mono solar cells.

SolarWorld solar cells have excellent performance characteristics even in low light conditions and higher efficiency and reliability.

Waterproof junction box is fitted with a blocking diode to prevent reverse current from the battery to the solar panel.

Me Solar modules with power higher than 50 W are fitted with 2 x 0.9 m cable specially designed for solar panels to carry high currents with very low power losses.

MC4 connectors are used for easy connectivity between the solar modules and the electronic equipment like solar charge controller.

Me Solar modules uses a 3.2mm thick tempered solar glass which makes it strong and durable.

The long-lasting, high-efficiency, monocrystalline solar cells and the tough, sealed, aluminium frame will give you years and years of consistent, free power.

This solar panel can be used in all weather conditions, including inland, marine applications and under hot or cold climate.

SPECIFICATIONS

	MESM-20W	MESM-30W	MESM-50W	MESM-80W	MESM-100W
Number of cells	36 (2x18)	36 (2x18)	36 (3x12)	36 (4x9)	36 (4x9)
Cell Type	Monocrystalline				
Maximum System Voltage	600 Vdc (IEC)			1000 Vdc (IEC)	

Electrical specifications *

Nominal Power	Pmax	20 Wp	30 Wp	50 Wp	80 Wp	100 Wp
Power output tolerance		± 3%	± 3%	± 3%	± 3%	± 3%

Maximum power voltage	V _{mpp}	17,80 V	17,80 V	17,80 V	17,80 V	17,80 V
Open Circuit Voltage	V _{oc}	22,30 V	22,30 V	22,30 V	22,30 V	22,30 V
Maximum power current	I _{mp}	1,12 A	1,69 A	2,81 A	4,49 A	5,62 A
Short Circuit Current	I _{sc}	1,21 A	1,82 A	3,03 A	4,85 A	6,07 A

Temperature Ratings

Open circuit voltage coefficient	T _k V _{oc}	-0,31 % / °C
Short circuit current coefficient	T _k I _{sc}	0,05 % / °C
Power coefficient	T _k P	-0,41 % / °C
Operating Temperature		-40 to +85 °C

Other specifications

Dimensions	mm	345 x 470 x 25	605 x 345 x 25	650 x 505 x 25	770 X 670 X 30	945 x 670 x 30
Weight		2,2 Kg	2,7 Kg	3,7 Kg	5,7 Kg	7,0 Kg
Conection box		Junction box with diodes				
Cable		None	None	900 mm	900 mm	900 mm
Connector		-	-	MC4	MC4	MC4
Warranty		Product: 2 years warranty under manufacturing defects				

* Standard Test Conditions STC (Air Mass AM1.5, Irradiance 1000W/m², Cell Temperature 25°C)

DOWNLOADS

CATÁLOGO GENERAL BORNAY 14-15

 [Catalogo-Bornay-1415.pdf](#) (10.41 MiB)
Size: 10.41 MiB

PANELES SOLARES ME ENERGY

 [Paneles solares Me Energy.pdf](#) (1.19 MiB)
Size: 1.19 MiB

ME SOLAR 20 W

 [20w mono datasheet.pdf](#) (2.95 MiB)
Size: 2.95 MiB

ME SOLAR 30 W

 [30w mono datasheet.pdf](#) (3.14 MiB)
Size: 3.14 MiB

ME SOLAR 50 W

 [50w mono datasheet.pdf](#) (3.7 MiB)
Size: 3.7 MiB

ME SOLAR 80 W

 [80w mono datasheet.pdf](#) (1.07 MiB)
Size: 1.07 MiB

ME SOLAR 100 W

 [100w mono datasheet.pdf](#) (921.1 KiB)
Size: 921.1 KiB
